




|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#            | <b>23942274</b>                                                                                                                                                                                                                                                                                                                                                                                                                    |
| article description | <b>CEE-switched interlocked socket compact 32A 4p 3h IP66/IP67</b>                                                                                                                                                                                                                                                                                                                                                                 |
| description long    | CEE-switched interlocked socket compact 32A4p 3h IP66/IP67<br>housing material: PA6 + PC/ABS<br>rated current: 32A<br>number of poles: 4 (3P+PE)<br>clock-position: 3h<br>rated voltage/frequency: 380/440V~ / 50/60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>wall mounting, mechanical interlock<br>switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA<br>IP protection class: IP66/IP67 |
| GTIN (EAN)          | 9003399174988                                                                                                                                                                                                                                                                                                                                                                                                                      |
| country of origin   | AT                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| customs number      | 85366990                                                                                                                                                                                                                                                                                                                                                                                                                           |
| net weight          | 0.713 kg                                                                                                                                                                                                                                                                                                                                                                                                                           |
| packaging quantity  | 1                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                           |                          |
|---------------------------|--------------------------|
| ETIM 7.0                  | EC001324                 |
| IEC-amperage              | 32 A                     |
| Number of poles           | 4                        |
| Voltage acc. EN 60309-2   | 400-440 V (50+60 Hz) red |
| Clock hour position       | 3 h                      |
| Identification colour     | Red                      |
| Degree of protection (IP) | IP67                     |
| Switch                    | Mechanical locking       |
| Material housing          | Plastic                  |
| Model                     | Base unit and cover      |
| Contact material          | CuZn                     |
| Surface finish contacts   | Nickel-plated            |

|               |                        |
|---------------|------------------------|
| wire flexible | 2,5-6 mm <sup>2</sup>  |
| wire solid    | 2,5-10 mm <sup>2</sup> |



Descargá el catálogo